

MM-270-01

PinBrazing Unit Chargers

ECONECT Charger



- 400W mobile power
- Sturdy metal enclosure
- Auto switch off at full battery
- Load-controlled cooling fan

Technical Specification

Charge Current	7,5A
Battery type	LiFePO4
Output Power	400W max.
Operating Temperature	-0°C to +40°C @100VAC
Mains-In	100-240VAC/50-60Hz
DC-Out	1.2m charge cord with Neutrik NL4FX
Dimensions WxDxH	158x235x67mm
Weight	2.3kg
Agency Approvals	CE

Part no. 8048

ECONECT Car charger



- Auto turns off when DC input drops below 13,0V
- Sturdy metal enclosure
- Load-controlled cooling fan
- Automatic float charging

Technical Specification

Charge Current	2,0A
Battery type	LiFePO4
Output Power	90W max.
Operating Temperature	-0°C to +40°C
Mains-In	12VDC
Dimensions WxDxH	111x120x61mm
Weight	1.0kg
Agency Approvals	CE

Part no. 80561

S30 X/C Charger



- Automatic float charging
- Sturdy metal enclosure
- Protection against reverse polarity & short circuit with spark suppression
- Load-controlled cooling fan

Technical Specification

Charge Current	7,0A
Battery type	Lead/Acid Batteries
Output Power	375W max.
Operating Temperature	-0°C to +40°C
Mains-In	100-240VAC/50-60Hz
DC-Out	1.2m charge cord with Neutrik NL4FX
Dimensions WxDxH	112x226x52mm
Weight	1.4kg
Agency Approvals	CE

Part no. 8049

S30 X/C Car charger



- Auto turns off when DC input drops below 13,0V
- Sturdy metal enclosure
- Load-controlled cooling fan
- Automatic float charging

Technical Specification

Charge Current	2,0A
Battery type	Lead/Acid Batteries
Output Power	90W max.
Operating Temperature	-0°C to +40°C
Mains-In	12VDC
Dimensions WxDxH	111x120x61mm
Weight	1.0kg
Agency Approvals	CE

Part no. 8055